


Reference	NR/L2/CIV/003
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

## Level 2

# Engineering Assurance of Building and Civil Engineering Works

### Endorsement and Authorisation

Endorsed by:



K Brady, Working Group Chair

Authorised by:



N Ricketts, Professional Head (Buildings and Civils)

Accepted for issue by:



M. McManus, National Standards Manager

This document is the property of Network Rail. It shall not be reproduced in whole or part nor disclosed to a third party without the written permission of the Standard Owner.

© Copyright 2012 Network Rail.

Uncontrolled copy once printed from its electronic source.

Published and issued by Network Rail Kings Place, 90 York Way London N19AG.



Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

## User information

This standard contains colour-coding according to the following Red–Amber–Green classification.

### **Red requirements – No deviations, could stop the railway**

- **Red requirements shall** always be complied with and achieved.
- Red requirements shall be presented in a red box **with the word “shall” or expressed as a direct instruction**.
- Accountability for the efficacy of red requirements lies with the Professional Head/Standard Owner.
- Red requirements are monitored for compliance.
- Corrective actions shall be enforced if deviations are discovered through functional checks (e.g. engineering verification visits, audit or Operations Self-Assurance).

### **Amber requirements – Controlled deviations, approved risk analysis and mitigation**

- **Amber requirements shall** be complied with unless deviation has been approved in advance.
- Amber requirements shall be presented with an amber sidebar **and with the word “shall” or expressed as a direct instruction**.
- Accountability for the efficacy of these requirements lies with the Professional Head/Standard Owner, or their nominated Delegated Authority.
- Amber requirements are monitored for compliance.
- Deviations **may** be permitted. Deviations are approved by the Standard Owner or through existing Delegated Authority arrangements.
- Corrective actions shall be enforced if **non-approved** deviations are discovered through functional checks (e.g. engineering verification visits, audit or Operations Self-Assurance).

### **Green – Guidance**

- Guidance is based on good practice. Guidance represents supporting information to help achieve **Red** and **Amber** requirements.
- Guidance shall be presented with a dotted green sidebar **and with the word “should” (usually in notes) or as a direct instruction**.
- Guidance is **not mandatory** and is not monitored for compliance.
- Alternative solutions may be used. Alternative solutions do not need to be formally approved.
- Decisions made by a competent person to use alternative solutions should be backed up by appropriate evidence or documentation.

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

## Issue record

Issue	Date	Comments
1	October 2001	Supersedes RT/CE/P/003
2	February 2004	Supersedes RT/CE/S/003 Issue 1
3	June 2011	Updated to reflect changes to the organisation and streamlining of Technical Approval procedure.
4	June 2012	Editorial edits to eliminate typographical errors, improve clarity and capture feedback gained from the briefing out process and usage of Issue 3.

## Compliance

This Network Rail standard is mandatory and shall be complied with by Network Rail and its contractors if applicable from 1<sup>st</sup> September 2012.

When this standard is implemented, it is permissible for all projects that have formally completed GRIP Stage 3 (Option Selection) to continue to comply with the issue of any relevant Network Rail standards current when GRIP Stage 3 was completed and not to comply with requirements contained herein, unless stipulated otherwise in the scope of this standard.

## Reference documentation

### Network Rail standards

<a href="#">NR/L2/EBM/STP001</a>	Network Rail standards management - Process requirements
<a href="#">NR/L2/INI/02009</a>	Engineering management for projects
<a href="#">NR/L2/INI/CP0047</a>	Application of the Construction Design and Management Regulations to Network Rail Construction Works
<a href="#">NR/L2/INI/CP0069</a>	Route requirement management and engineering remit production
<a href="#">NR/L1/INI/PM/GRIP/100</a>	Governance for Railway Investment Projects (GRIP) - Policy
<a href="#">NR/L3/CIV/006</a>	Handbook for the examination of structures
<a href="#">NR/L3/CIV/151</a>	Engineering Assurance of Standard Designs and Details for Building and Civil Engineering Works

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

### Forms associated with this standard

<a href="#">NR/L2/CIV/003/F001</a>	Approval in Principle
<a href="#">NR/L2/CIV/003/F002</a>	Statement of Design Intent
<a href="#">NR/L2/CIV/003/F003</a>	Certificate of Design and Check
<a href="#">NR/L2/CIV/003/F004</a>	Architectural and layout acceptance
<a href="#">NR/L2/CIV/003/F005</a>	Certificate of fitness to be taken into use
<a href="#">NR/L2/CIV/003/F006</a>	Roads/Highways Authority Agreement to Bridgeworks
<a href="#">NR/L2/CIV/003/F1990</a>	Technical Design Requirements for BS EN 1990
<a href="#">NR/L2/CIV/003/F1991</a>	Technical Design Requirements for BS EN 1991
<a href="#">NR/L2/CIV/003/F1992</a>	Technical Design Requirements for BS EN 1992
<a href="#">NR/L2/CIV/003/F1993</a>	Technical Design Requirements for BS EN 1993
<a href="#">NR/L2/CIV/003/F1994</a>	Technical Design Requirements for BS EN 1994
<a href="#">NR/L2/CIV/003/F1997</a>	Technical Design Requirements for BS EN 1997

### Other references

New Roads and Street Works Act 1991

The Construction (Design and Management) Regulations 2007 (SI No. 320)

*Technical Approval of Highway Structures* (Design Manual for Roads and Bridges:  
Department for Transport

### Disclaimer

In issuing this document for its stated purpose, Network Rail makes no warranties, express or implied, that compliance with all or any documents it issues is sufficient on its own to ensure safe systems or operation. Users are reminded of their own duties under health and safety legislation.

### Supply

Copies of documents are available electronically, within Network Rail's organisation. Hard copies of their document may be available to Network Rail people on request to the relevant controlled publication distributor. Other organisations may obtain copies of this document from IHS. Tel: 01344 328039.

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

## Contents

1	Purpose	6
2	Scope	6
3	Roles and responsibilities	7
4	Definitions and abbreviations	7
5	Procedure	10
6	Alterations to the Design	17
7	External stakeholders	17
	Appendix A Design Check Categories	18

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

## 1 Purpose

The purpose of this standard is to define the engineering assurance requirements for the Design and Construction of Works undertaken on Building and Civil Engineering infrastructure.

## 2 Scope

This standard applies to the following types of Works undertaken on B&C infrastructure (including Building Services) owned, or to be owned, by Network Rail.

- 1 Enhancements.
- 2 Replacements.
- 3 Repair Works - except where the Design of these is incorporated into the PRS (or similar specification provided by the Asset Manager) and there is no plan to appoint a Designer for implementation.
- 4 Emergency Works.
- 5 Temporary Works to facilitate the construction of permanent Works or staged construction, or to provide access for examination and inspection - and where the Temporary Works could have the same impact on the infrastructure as permanent Works.

This standard applies to Works undertaken by Network Rail on B&C infrastructure (including Building Services) owned by an Outside Party. The standard also applies to the Works undertaken on Outside Party infrastructure that is on, over or under Network Rail's infrastructure and where the Outside Party does not have an equivalent procedure to that defined in **5** (of this standard) for those Works. The procedure defined in the *Technical Approval of Highway Structures* is considered to be equivalent.

Network Rail has no power to enforce the requirements of this standard on Works undertaken on Outside Party infrastructure which lies entirely outside Network Rail's infrastructure - whether or not such Works could affect railway operations. For such Works, reasonable endeavours can be followed to apply the requirements of this standard or to obtain confirmation from the Outside Party that there is an equivalent procedure to that defined in **5** in place. Where an Outside Party follows the requirements of this standard, it is acceptable to use documents that are equivalent to the Sponsor's Instruction, PRS and CR-T, and modified versions of the Forms associated with this standard.

This standard does not apply to:

- 1 Consents or approvals from bodies outside Network Rail including;
  - regulatory and statutory authorities
  - planning, listed building and conservation authorities

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

- environmental agencies
  - land and property owners or leaseholders
  - statutory undertakers and other public services and utilities owners.
- 2 Obtaining approvals for the New Roads and Street Works Act.
  - 3 Obtaining approval from other Network Rail engineering disciplines for the equipment carried by ESS (such as for signal sighting and reduced clearances), or for the performance of that equipment.
  - 4 Non-structural aspects of Building Works (other than Building Services) - such as the general layout, means of escape, architectural fixtures and finishes - unless the PRS requires such aspects to be covered through the submission of [NR/L2/CIV/003/F004](#).
  - 5 Assessments of structures.

### 3 Roles and responsibilities

#### **Asset Manager**

The Asset Manager is accountable for the management of Building and Civil Engineering infrastructure, and is responsible for producing the PRS (or similar specification) and providing Approval in Principle of the Single Option.

#### **Project Engineer (Building and Civil Engineering)**

The PE (B&C) is appointed in accordance with [NR/L2/INI/02009](#): *Engineering management for projects*, and is responsible for (a) the Building and Civil Engineering aspects of the Project, and (b) for following the requirements of this standard, including Acceptance of the Engineering Deliverables.

#### **Contractor's Responsible Engineer**

The role of the CRE extends to both the design and construction phases of a Project. The CRE is accountable for the day-to-day management and co-ordination of the technical and engineering activities within a specific engineering discipline for a specific Contract. The CRE is appointed in accordance with [NR/L2/INI/02009](#) and is (a) authorised to sign the Forms associated with this standard on behalf of the design and/or contracting organisation, and (b) responsible for confirming that the Engineering Deliverables satisfy the requirements of the Contract and also meet the requirements of this standard.

### 4 Definitions and abbreviations

#### **Acceptance (of Engineering Deliverables)**

Acceptance that the PE (B&C) is satisfied that:

- 1 The Deliverables have been checked and approved by the design organisation in accordance with this standard and with [NR/L2/INI/02009](#).
- 2 Appropriate standards and/or design criteria have been used.

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

- 3 An appropriate review has been carried out, based on an agreed risk level, to support the declaration by the CRE that the Deliverables comply with the specified requirements.

### **Approval in Principle (of the Single Option)**

Approval signifies that the Asset Manager is satisfied that the design solution identified is the preferred option for achieving the objectives of the Project and the PRS.

### **Approved for Construction**

A Design that has been prepared, checked and approved in accordance with the Contract requirements and relevant standards - including [NR/L2/INI/02009](#).

### **Building and Civil Engineering (B&C) infrastructure**

The infrastructure for which Network Rail's Professional Head (B&C) is responsible for providing technical support.

### **Building Services**

Apparatus and equipment used to provide ventilation, heating and cooling, lighting, plant, gas, water, power and drainage to a building.

### **Checker**

The person, appointed in accordance with [NR/L2/INI/02009](#), who is authorised to sign [NR/L2/CIV/003/F003](#) on behalf of the checking organisation.

### **Construction Work**

Activities defined as 'construction work' in the Construction (Design and Management) Regulations and [NR/L2/INI/CP0047](#). The term excludes inspection and examination activities.

### **Contractor's Responsible Engineer (CRE)**

### **Contract Requirements - Technical (CR-T)**

The technical requirements included in implementation contracts. The CR-T can include additional Engineering Deliverables to those produced to support the Approval in Principle of the Single Option. The term also refers to requirements that are specified for in-house delivery.

### **Design**

A Design comprises the drawings, layout and connection details, specifications and bill of quantities (including the specification of articles or substances) relating to the Works, and calculations undertaken to support these items.

### **Design Check**

A check of a Design to confirm its adequacy. The Design Check is carried out by an independent Checker, and includes verifying compliance with the CR-T.

### **Designer**

The CRE appointed in accordance with [NR/L2/INI/02009](#) and who is authorised to sign, on behalf of the Design Organisation, [NR/L2/CIV/003/F001](#); [F002](#); and [F003](#).



Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

### **Emergency Work**

Work carried out as part of an immediate response to an incident, and which restores the fitness for purposes of railway operations and/or infrastructure.

### **Engineering Deliverables**

Designs, specifications, reports, certificates, data, and other information that fulfil the requirements of the PRS.

### **Enhancement**

Works delivered through a Project that change the operational capability of the infrastructure.

### **Equipment Support Structures (ESS)**

Structures whose function is to support and provide access to signalling, telecommunication, power equipment, etc.

### **Hidden Part**

A primary structural member that cannot be observed from at least one side throughout its extent and which is not protected by a material that can preserve its condition.

### **Outside Party**

An organisation, other than Network Rail, that is an infrastructure owner or developer, or a user or occupier of Network Rail's infrastructure. The term includes highway authorities, passenger transport executives, public or private developers, and train operating companies.

### **Project Engineer (Building and Civil Engineering): PE (B&C)**

### **Project Requirements Specification (PRS)**

A technical specification of engineering requirements produced by the Asset Manager and issued to the delivery organisation by the Sponsor as part of the Sponsor's Instruction.

### **Repair Work**

Planned work that requires reinstatement of the components of a structure, but which does not result in a permanent change to the general form of that structure or a permanent reduction of the structure gauge or standard of safety. The term includes;

- like-for-like repairs and replacement of components,
- repair and replacement of components in similar or generally accepted equivalent materials provided that such substitution does not affect the integrity or performance of the structure, and
- 'good housekeeping' activities such as cleaning, painting, pointing, removal of harmful vegetation from structures, and clearing mud and silt from watercourses.

### **Replacement**

Works that involve the replacement of a structure (or part of one) where there is no change to the functionality of that structure.

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

### **Sponsor's Instruction**

The formal document from the Sponsor that describes the objectives for each stage of a Project and details the services to be provided by the Project Manager.

### **Taken into Use**

The state of new, altered, or renewed infrastructure or Temporary Works (whether complete or not) when fit for (as applicable) the safe passage of trains; occupation by users; use of or passage by members of the public; and installation of plant or equipment.

### **Temporary Works**

Structures or staging works that enable construction work to be carried out and which are removed or become redundant before the completion of the permanent Works. Temporary Works include;

- existing structures subjected to a temporary load which is higher than that normally experienced by the structure,
- access scaffolding and falsework,
- temporary structures that provide access for inspection and/or examination only,
- excavations,
- demolition - where this not part of the Project Works, and
- partially completed structures which are subjected to substantial temporary loads.

## **5 Procedure**

### **5.1 Project phases**

In sequence, **5.2** to **5.8** define the acceptance procedures for:

- 1 Sponsor's Instruction for development.
- 2 Approval in Principle of the Single Option.
- 3 Updating the Sponsor's Instruction for Implementation.
- 4 Contract Requirements -Technical.
- 5 Design.
- 6 Design Check.
- 7 Verification and entry into service.

In following these procedures, reference should be made to the GRIP stages defined in [NR/L1/INI/PM/GRIP/100](#): *Governance for Railway Investment Projects (GRIP) - Policy*.

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

## 5.2 Sponsor's Instruction for development

A Sponsor's Instruction shall be prepared for each Project. The Instruction shall include the PRS (produced in accordance with [NR/L2/INI/CP0069](#): *Route requirement management and engineering remit production* and include the requirements specified by the Asset Manager. The Instruction and PRS should be issued at the start of GRIP 2 and be updated as required during the lifecycle of the Project.

## 5.3 Approval in Principle of the Single Option

With some exceptions, described below, Design work shall not commence prior to the granting of Approval in Principle of the Single Option - as regulated through [NR/L2/CIV/003/F001](#). Where this Form is required for the Works, no change to the configuration of the infrastructure shall take place until Approval in Principle has been granted.

Form [NR/L2/CIV/003/F001](#) shall be submitted by the PE (B&C) to the Asset Manager for signed Acceptance when a Project has developed to a stage that a Single Option has been determined and the PRS requirements have been defined. This Form shall also be signed by the PE (B&C) and the CRE of the Design organisation.

Where more than one B&C discipline is involved, signed Approval shall be obtained from Asset Managers in each of those disciplines. Depending on the scale and complexity of the Project, it might be necessary to submit separate [NR/L2/CIV/003/F001](#) for (for example), (a) structural Works, and (b) the provision of Building Services.

Where an Interdisciplinary Review is required, it shall be prepared in accordance with [NR/L2/INI/02009](#) prior to the submission of the [NR/L2/CIV/003/F001](#) to the Asset Manager.

The following information shall be provided as part of or in addition to the [NR/L2/CIV/003/F001](#):

- 1 In A1.2, details of the Design criteria that are not covered in current standards, and criteria that are not normally used or are maintenance choices that have not been specified by the Asset Manager.
- 2 In A1.2, as required, references to the *Technical Design Requirements Forms* ([NR/L2/CIV003/F1990](#) to [F1997](#)) and the decisions on the options selected for applying the suite of Structural Eurocodes.
- 3 In A1.3, details of anticipated deviations to standards and the justification for these: where necessary, these shall be agreed by the Professional Head (B&C). Formal approval for all deviations shall be obtained prior to submission of the [NR/L2/CIV/003/F003](#).

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

- 4 Details of Hidden Parts that are to be retained - including
  - a. in A1.6; a justification for their retention, investigations undertaken (or required to be undertaken) to determine their condition, and proposed remedial works to them, and
  - b. in A1.7 arrangements for the visual observation of these (in accordance with [NR/L3/CIV/006](#): *Handbook for the examination of structures*) and/or alternative techniques for verifying their structural integrity.
- 5 Details of Hidden Parts that will be introduced by the Works - including
  - a. in A1.6, a justification for their introduction, and
  - b. in A1.7, arrangements for the visual observation of these (in accordance with [NR/L3/CIV/006](#): *Handbook for the examination of structures*) and/or alternative techniques for verifying their structural integrity.

A copy of the details of all Hidden Parts shall be provided in an readily useable format (such as through as-built drawings) to the Asset Manager. (Details of Hidden Parts that are not available at the time of the submission of the [NR/L2/CIV/003/F001](#) shall be provided as part of or in addition to the [NR/L2/CIV/003/F002](#).)

- 6 In A1.8, the Design Check Category as proposed by the PE (B&C).
- 7 Supporting evidence for the selection of the Single Option - this shall include the items required by the PRS.

A completed [NR/L2/CIV/003/F001](#) remains valid for three years provided that construction works begins within that time.

Where construction work has not started within that time then, unless agreed otherwise by the relevant Asset Manager(s), a new Form shall be submitted: such agreements shall be recorded by the Asset Manager(s).

Approval in Principle is not required for the following types of Works;

- Repair Works,
- Emergency Works,
- Temporary Works, and
- those where the Design requires either a Category 0 or Ia Design Check (see 5.7).

Where the selection of Design Check Category 0 has been accepted by the Asset Manager (as confirmed in the PRS) it is permissible for the Design to proceed without a [NR/L2/CIV/003/F002](#) or [NR/L2/CIV/003/F003](#).

In such cases, in addition to the normal signatories, the CRE and the PE (B&C) shall sign off the Approved for Construction documents prior to their issue.

Design Check Category 0 is not appropriate for Designs that deviate from the requirements of Network Rail standards or Railway Group Standards.

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

#### 5.4 Updating of the Sponsor's Instruction for implementation

Where a Sponsor's Instruction is to be updated to take account of a PRS for implementation, reference to the requirements of the approved [NR/L2/CIV/003/F001](#) shall be included in that update.

For a Design requiring a Check Category III where there is an absence of standards or where guidance is required for the interpretation of standards, the Asset Manager shall consult the Professional Head (B&C) to define the requirements for inclusion in the PRS for implementation.

#### 5.5 Contract Requirements - Technical

The CR-T shall include the necessary deliverables to support the contracting strategy.

The PE (B&C) is responsible for aligning the requirements of the CR-T with those specified in the PRS.

#### 5.6 Design

The basis of the Design of the Works (or a specific part of them) shall be defined within the [NR/L2/CIV/003/F002](#).

Form [NR/L2/CIV/003/F002](#) shall be submitted by the CRE to the PE (B&C). The PE (B&C) should have provided signed acceptance of the Form prior to the start of the Detailed Design stage.

Where necessary, the Design of Building Services (for example) shall be integrated with other parts of the Design through an Interdisciplinary Check process in accordance with [NR/L2/INI/02009](#).

A single [NR/L2/CIV/003/F002](#) may be submitted where a Design is used repetitively for a generic group of ESS or similar groups of structures/services.

Where, for example due to the Contractor's delivery strategy, the Design of a particular structure is split into parts, the submissions shall be integrated through the appointment of a lead Designer and Checker. They shall submit single [NR/L2/CIV/003/F002](#) and [NR/L2/CIV/003/F003](#) for the Project.

The following information shall be provided in addition to or as part of [NR/L2/CIV/F002](#).

- 1 In 1.2, staging of the Works. This shall include details of the proposed stages and associated method of working and, where applicable, demonstrate the structural adequacy and inter-compatibility of new, altered, and existing structures at all stages of Construction.
- 2 In 1.3, as required, reference to the *Technical Design Requirements Forms* ([NR/L2/CIV003/F1990](#) to [F1997](#)) and the decisions on the options selected for applying the Structural Eurocodes.

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

- 3 In 1.5, details of the deviations to standards: the process defined in [NR/L2/EBM/STP001](#): *Network Rail standards management - Process requirements* shall be followed.
- 4 The aspects applicable to the Design; this shall be done by striking through the non-applicable items given in the Design Checklist.
- 5 The nature and extent of parts/elements of existing structures/services that are to continue in use in association with new construction. This shall show how the suitability of these parts/elements for continuing use has been, or will be, addressed.
- 6 Where necessary (see points 4 and 5 of **5.3**),
  - a. in A1.6, additional details of Hidden Parts that will be retained or introduced through the Design, and
  - b. in A1.7, arrangements for the visual observation of these (in accordance with [NR/L3/CIV/006](#): *Handbook for the examination of structures*) and/or alternative techniques for verifying their structural integrity.  
A copy of the details of all Hidden Parts shall be provided in an readily useable format (such as through as-built drawings) to the Asset Manager.
- 7 The use of previously-designed structural parts/elements: a copy of the engineering assurance documents for these shall be appended.
- 8 The use of Standard Designs and Details - as defined in [NR/L3/CIV/151](#): *Engineering Assurance of Standard Designs and Details for Building and Civil Engineering Works*.

Where the PE (B&C) identifies deviations from the PRS, the appropriate Asset Manager shall review, amend (where necessary) and accept the deviations described in [NR/L2/CIV/003/F002](#) (PART 5).

In such cases, the Asset Manager may request the resubmission of [NR/L2/CIV/003/F001](#) to take account of changes to the PRS.

Where the PRS requires the submission of [NR/L2/CIV/003/F004](#), the Form shall be submitted in accordance with the stated requirements.

The requirements of this Clause (**5.6**) shall be applied to the Design of Temporary Works whose failure or presence could affect the safety of the railway or the safety of any persons other than those under the control of the construction organisation.

## 5.7 Design Check

### 5.7.1 Fundamental requirements

The Design submission shall be prepared to a sufficient level of detail to allow it to be issued as Approved for Construction. The submission shall include the drawings, schedules, performance, materials, workmanship specifications, testing and inspection plans, CDM risk registers, and other documents that form the Design.

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

Form [NR/L2/CIV/003/F003](#) shall be submitted by the CRE. This shall confirm that the Design has been (a) carried out in accordance with [NR/L2/CIV/003/F002](#), and (b) checked in accordance with the agreed Design Check Category. In addition, the CRE shall confirm the matters that have been considered in the Design Check by completing the Design Checklist that forms part of [NR/L2/CIV/003/F003](#).

### 5.7.2 Check Category

The Design Check Category should be in accordance with Table 1 but where it is apparent that a higher Check Category is appropriate, the PE (B&C) may amend the Category in the [NR/L2/CIV/003/F002](#).

Category	Type of Designs	Method of Checking
0	Designs for which calculations are not required, and the Design can be adequately checked by inspection. Designs shall meet the requirements of Network Rail standards and Railway Group Standards. Designs for which, although simple calculations can be required, the consequences of failure would not be significant.	No additional requirements.
Ia and Ib	Standard or simple Designs using simple methods of analysis and where all aspects of Design are in accordance with relevant standards. Assemblies of elements or components which have themselves been designed and checked and/or accepted.	The Design may be checked in the same Design team but by staff other than the Designers. The Checker may refer to the Design calculations and the assumptions on which the calculations are based. The Checker shall consider the Designer's assumptions to be valid.
II	Designs not in Categories 0, I or III.	The Design may be checked in the same organisation as that which prepared the Design. Checking shall be undertaken in a group or team that has not been concerned with the development of the Design.
III	Complex or unusual Designs, or which involve significant departures from current standards, novel methods of analysis or considerable exercise of engineering judgement.	The Design shall be checked by an organisation independent of the Design organisation (that is, by an organisation which is a separate legal entity).

**Table 1: Design Check Categories**

Examples of Check Categories for different types of Works are given in Appendix A.

Except where permitted in Table 1, the Design Check shall be carried out without reference to the Design calculations.



Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

Designs carried out by a Design organisation appointed by the Construction organisation to provide Design services should be checked at the levels shown in Table 1.

Table 1 shall be used with the following revisions;

- Category I Designs shall be checked as Category II Designs,
- Category II Designs shall be checked as Category III Designs,

where the Design;

- 1 is for a new generic Standard Design and Detail for incorporating into [NR/L3/CIV/151](#), or
- 2 is delivered by an organisation contracted by Network Rail to deliver both Design and Construction and the Design organisation and Construction organisations are not separate legal entities, or
- 3 is for an Outside Party.

### 5.7.3 Category III Design Check

When the PE (B&C) has identified that the method of Design is novel, the Checker shall not use the same method for completing the Design Check as used in the Design, but shall use recognised methods for the Check.

Where possible, Category III Checkers shall use different software to those used by the Designers: the PE (B&C) shall be advised where this is not feasible.

The PE (B&C) shall be provided with a Design Check statement that describes the proposed methodology for completing the Design Check.

The Design Check statement shall:

- describe the method of analysis to be used (including the use of computer-based methods),
- define the programme for the Design Check (including interfaces with the Designer), and
- state how compliance with the requirements of the Design Check will be achieved.

## 5.8 Verification and entry into service

Before any significant part of the permanent or Temporary Works for a Project are Taken into Use, Form [NR/L2/CIV/003/F005](#) for those Works shall be signed by the CRE (or their nominated representative).

When required by the PE (B&C), the CRE shall identify any necessary materials and commissioning tests required to verify that the Works is compliant with the Design.



Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

When the Work is carried out during periods when normal train operations are suspended or when other means of maintaining the safety of the operational railway are utilised, and such Work is to be Taken into Use (whether the permanent Works are completed or not), the completed [NR/L2/CIV/003/F005](#) shall be provided to the person responsible for the provision of access within 3 metres of the track.

## 6 Alterations to the Design

Alterations to a Design which materially affect the statements made in a [NR/L2/CIV/003/F002](#) shall lead to a resubmission of that Form. This will also require a resubmission of the [NR/L2/CIV/003/F003](#) (where it is in place).

Where reasonably practicable, a proposed change to a Design shall not be implemented until a revised version of [NR/L2/CIV/003/F002](#) for the change has been accepted by Network Rail. Other Design Changes shall be undertaken using the change control process set out in [NR/L2/INI/02009](#).

When significant changes to a Design are necessary during possessions or at other times where it is impracticable for the Design change to be accepted by Network Rail before implementation, the Design change shall be reviewed by the PE (B&C), and any additional mitigation measures agreed and put into place before the works are Taken into Use. In such cases, the Design change shall be checked, and a revised version of [NR/L2/CIV/003/F003](#) reissued with the Design to Network Rail for acceptance within 3 days of the Works (permanent or Temporary) being Taken into Use.

## 7 External stakeholders

### 7.1 Public Road, Bridleway, Footpath Bridges, and Outside Party structures

When the Works affect (a) a bridge carrying a public road, bridleway or footpath, and/or (b) an Outside Party structure, the agreement of the relevant road/highway authority or structure owner shall be obtained and recorded at the Approval in Principle stage.

For bridges carrying a public road, bridleway, or footpath, this may be done by submitting Form [NR/L2/CIV/003/F006](#) to the road/highway authority (for their signed approval).

### 7.2 Leased structures

When the Works affect a Station, Depot or other Network Rail property leased to a train or freight operating company or other organisation, where possible the comments of the company or organisation shall be requested and included in the submission of [NR/L2/CIV/003/F001](#).

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

## Appendix A Design Check Categories

### A1 Applicability of Forms

The applicability of the Forms to the various Design Check Categories is described in Table A1.

Form	Applicable stage	Design Check Category
NR/L2/CIV/003/F001: <i>Approval in Principle</i>	Upon selection of single option	Ib, II, III
NR/L2/CIV/003/F002: <i>Statement of Design Intent</i>	Prior to start of Detailed Design	Ia, Ib, II, III
NR/L2/CIV/003/F003: <i>Certificate of Design and Check</i>	At completion of Detailed Design	Ia, Ib, II, III
NR/L2/CIV/003/F005: <i>Certificate of fitness to be taken into use</i>	Prior to entry into service	0, Ia, Ib, II, III

**Table A1: Applicability of Forms**

### A2 Selection

The following indicates the Design Check Category that is generally applicable for the types of Works listed.

In all cases, however, appropriate engineering judgement shall be exercised when selecting the Category.

It is assumed in the listing that the following apply: average soil conditions; conventional types of construction; and normally accepted serviceability criteria. Consideration shall be given to elevating the Category where any of the following apply;

- soil conditions are unusual, and/or the soil has a low strength or high compressibility,
- the type of construction is unusual,
- deflections are critical, such as when the proposed Works are adjacent to an existing track or structure.

For many Works with Design Check Category 0 (particularly where calculations are not done), a suitable Work Package Plan can be sufficient to describe and control the design parameters (general form, materials, clearances etc).

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

The use of Standard Designs and Details shall be in accordance with [NR/L3/CIV/151](#).

## **Permanent Works**

### **Category 0**

Emergency works that are determined without Design calculations  
 Surface car parks (unless extensive)  
 Drainage works that do not require hydraulic design  
 Earth-retaining structures with a retained height not exceeding 600 mm and in locations (such as the toe of a cutting) where their failure would not obstruct the passage of trains  
 Fencing, security palisade fencing, safe access walkways  
 Painting  
 Waterproofing of bridge decks  
 Brickwork re-pointing  
 The superstructure of modular platforms (for supporting lineside equipment) that are to be installed according to the manufacturer's recommendations (foundations are categorised separately)

### **Category 1a**

Bespoke designs of the superstructure of modular platforms (for supporting lineside equipment) supported on spread footings on natural undisturbed ground  
 Platforms less than 3.5m wide supported on spread footings on natural undisturbed ground  
 Bespoke buildings of two storeys or less with one plan dimension of 6.0m or less, and which are supported on spread footings  
 Emergency Works determined with Design calculations  
 Structures with a span of 5.0m or less, and which can be built without requiring a possession

#### **Signalling**

Superstructures: straight post, signal post, OLE mesh, bespoke elevated structure (LOC platform, SPT walkway), speed sign post, ground position light signal, level crossing elements, gallows structure for banners  
 Foundations: spread foundations for the above superstructures and REB, URX, undertrack crossings  
 Earth-retaining structures with a retained height not exceeding 1m

#### **Telecoms**

Superstructures: brackets supporting telecom display units, gallows structure for OFF Indicator or for NTI  
 Foundations: spread foundations to the above superstructures, DOO camera column, or DOO monitor stacked housing

#### **Electrification**

Spread concrete foundations (bases) supporting DNO, auxiliary transformer, mobile generator, PSP, points heating cubicle, points heating transformer, points heating terminal box, functional supply point

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

### **Category Ib**

Bridge superstructure whose Design is based closely on one previously certificated with Design Check category II or III (that is, one with no more than minor modifications)

Single span simply-supported slab or deck-type bridge superstructures with a span not exceeding 15m and a skew not exceeding 20°

Footbridges of conventional construction with a span not exceeding 20m

Portal structures of conventional construction with a span not exceeding 20m

Culverts of conventional construction

Reinforced concrete box culverts with a span not exceeding 6m

Gravity earth-retaining walls with a retained height not exceeding 5m

Soil stabilisation works involving toe weighting, sheet piling or bored piles

Station platforms on level or near-level ground, or in cuttings

Single-storey buildings and platform canopies of conventional construction

Drainage works that require hydraulic design

### **Category II**

Works not in Design Check Category 0, I or III

### **Category III**

Bridges and other structures with a high degree of redundancy

Bridges with a span exceeding 50m

Bridges with a skew exceeding 45° or lead exceeding half the span except

- where the Design is based closely on a Design previously certificated Design Check Category III (that is one with no more than minor modifications)
- for simply-supported torsionally-flexible types of bridge decks - such as half-through girders with a steel floor

Bridges and other substantial structures with difficult foundation conditions

Complex, unusual or innovative geotechnical works (including cutting or embankment stabilisation Works through difficult ground conditions)

New tunnels

Substantial Works in existing tunnels or tunnel shafts (other than conventional lining works - such as the replacement of a brick ring or the spraying of concrete)

New and altered structures with non-standard loading conditions

Where the Design involves consideration of the aerodynamic effects of trains travelling at speeds greater than 125mph

Works which include structural features or characteristics that have not previously been used and which will be subject to railway live loading

Other Works that the Asset Head, Asset Manager, Project Engineer, or Professional Head (B&C) consider to be in Design Check Category III

## **Temporary Works**

### **Category 0**

Proprietary falsework systems or access towers used in accordance with the manufacturer's recommendations

Temporary pedestrian edge protection to excavations etc. for use only by persons under the control of the construction organisation

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

Ground support for scaffolding, access towers, small crane lifts and the like where loading is modest and the substrate is competent

Minor unsupported (vertical-sided or battered) excavations, including

- normal service trenches
- other excavations up to about 1 square metre in plan (where subject to railway or road vehicular live loading not exceeding about 600mm in the direction of traffic)

### ***Category Ia***

Proprietary previously-designed road vehicle bridge or footbridge superstructure systems used at the rated loading, and used in accordance with the manufacturer's recommendations  
 Single-level propped soil-retaining structures  
 Cantilever soil-retaining structures with a retained height not exceeding 3m  
 Reinforced soil structures with a retained height not exceeding 3m  
 Temporary level crossings  
 Demolition of single-span arch bridges  
 Temporary pedestrian edge protection to excavations etc. for public use  
 Tube-and-fitting scaffolding supported on the ground, not more than 6m high and not spanning more than 3m

### ***Category II***

Multi-level-propped soil-retaining structures  
 Anchored soil-retaining structures up to 6m retained height  
 Cantilever soil-retaining structures with a retained height not exceeding 6m  
 Reinforced soil structures with a retained height not exceeding 6m  
 Shield-driven tunnels up to 4.5m diameter  
 Jacked undertrack structures up to 6m span  
 Temporary station platforms  
 Temporary road vehicle bridges and footbridges (other than proprietary superstructure systems as given for Category I)  
 Tube-and-fitting scaffolding not supported on the ground (e.g. suspended from a structure), and/or more than 6m high and/or spanning more than 3m  
 Demolition of multi-span arch bridges

### ***Category III***

Temporary track alignments  
 Temporary bridges carrying rail traffic  
 Structures that exceed the limits for Design Check Category II  
 Other Works that the Asset Head, Asset Manager, Project Engineer, or Professional Head (B&C) consider to be in Design Check Category III

### ***Category Ia, II or III (to be determined on a site-specific basis)***

Ground support/foundations for; large crane lifts, proprietary road vehicle bridge, footbridge superstructure systems, temporary bridges carrying rail traffic, other temporary structures  
 Unsupported (vertical-sided or battered) excavations that exceed the limits for Design Check Category 0  
 Temporary Works at risk of impact by road vehicles or construction traffic

Reference	<b>NR/L2/CIV/003</b>
Issue	4
Publication date	2 <sup>nd</sup> June 2012
Compliance date	1 <sup>st</sup> September 2012

## **Building Services (Permanent or Temporary Works)**

### **Category 0**

Like-for-like building renewals whose design/arrangements are based on National Building Regulations (for example) - so that they do not require a detailed Design - and which do not affect the kinetic envelope or clearances to trains

### **Category Ia or Ib**

Where the Design is undertaken to *The Chartered Institute of Building Services Engineers Guides*, or a similar national building specification approved by the Asset Head

### **Category II**

Works not in Design Check Category 0, I or III

### **Category III**

Other Works that the Asset Head, Asset Engineer, Project Engineer, or Professional Head (B&C) consider to be in Design Check Category III.

## Standards Briefing Note

Ref: NR/L2/CIV/003		Issue: 4							
Title: Engineering Assurance of Building and Civil Engineering Works									
Publication date: 02/06/2012		Compliance date: 01/09/2012							
Standard Owner: Professional Head (B&C), Asset Management (B&C)									
Non-Compliance rep (NRNC): Senior Policy Development Specialist, Asset Management (B&C)									
Further information contact: Ken Brady, Senior Policy Development Specialist, Asset Management (B&C)			Tel: 0207 557 8367						
<b>Purpose:</b> The purpose of this standard is to define the Engineering Assurance requirements for the design and construction of works undertaken on Building and Civil Engineering infrastructure.		<b>Scope:</b> This standard applies to the following types of Works undertaken on B&C infrastructure (including Building Services) owned, or to be owned, by Network Rail <div><div>1</div>Enhancements.<div>2</div>Replacements.<div>3</div>Repair Works - except where the design of these is incorporated into the PRS (or similar specification provided by the Asset Manager) and there is no plan to appoint a Designer for implementation.<div>4</div>Emergency Works.<div>5</div>Temporary Works to facilitate the construction of permanent Works or staged construction, or to provide access for examination and inspection - and where Works could have the same impact on the infrastructure as permanent Works.</div> This standard applies to Works undertaken by Network Rail on B&C infrastructure (including Building Services) owned by an Outside Party. The standard also applies to the Works undertaken on Outside Party infrastructure that is on, over or under NR's infrastructure and where the Outside Party does not have an equivalent procedure to that defined in the standard.							
<b>What's New/ What's Changed and Why:</b> A number of editorial changes have been made to improve the clarity of text and to address issues raised through the extensive briefing out process undertaken for the previous issue (3) of this standard. Such changes include corrections to the text to cover (a) the Design Check category for Temporary Works, and (b) references to the <i>Technical Design Requirements</i> for the suite of structural Eurocodes. In addition, text has been incorporated from NR/BS/LI/189: <i>Additional requirements relating to hidden parts</i> . The improved clarity of text will reduce the number of queries on the standard, and improve its application.									
<b>Affected documents:</b> <table><tr><td>Reference</td><td>Impact</td></tr><tr><td>NR/L2/CIV/003 ISSUE 3</td><td>Superseded</td></tr><tr><td>NR/BS/LI/189 ISSUE 1</td><td>Withdrawn</td></tr></table>				Reference	Impact	NR/L2/CIV/003 ISSUE 3	Superseded	NR/BS/LI/189 ISSUE 1	Withdrawn
Reference	Impact								
NR/L2/CIV/003 ISSUE 3	Superseded								
NR/BS/LI/189 ISSUE 1	Withdrawn								
<b>Briefing requirements:</b> <i>Where Technical briefing (T) is required, the specific Post title is indicated. These posts have specific responsibilities within this standard and receive briefing as part of the Implementation Programme. For Awareness briefing (A) the Post title is not mandatory.</i> Please see <a href="http://ccms2.hiav.networkrail.co.uk/webtop/drl/objectId/09013b5b804504da">http://ccms2.hiav.networkrail.co.uk/webtop/drl/objectId/09013b5b804504da</a> for guidance.									
<b>Briefing</b> (A-Awareness/ T-Technical)	<b>Post</b>	<b>Team</b>	<b>Function</b>						
A	Route Asset Managers (Structures, Buildings, Geotechnics, Civils)	Route Asset Management teams (B&C)	Asset Management (B&C)						
A	Head of B&C Programmes; Head of Civils Asset Management (Structures); Programme Manager; Senior Compliance Management Engineer; Structures Management Engineer	Central Asset Management (B&C)	Asset Management (B&C)						
A	Senior Project Engineers, Senior Programme Engineers, Senior Design Engineers, Programme Engineering Managers, Programme Engineers, Project Engineers, Principal Design Engineers, Design Engineers & Assistant Project Engineers, Principal Project Engineer - FTN, Principal [Structures] Design Engineer - Crossrail	All Buildings and Civils teams	Investment Projects						

\*NOTE: Contractors are responsible for arranging and undertaking their own Technical and Awareness Briefings in accordance with their own processes and procedure