

Route Requirements Document Cambridgeshire Phase 1 & 2 TWAO – Mainline & Branchline Route Requirements Document Template ref: NR/PSE/FRM/0240, Issue 03, 20th March 2014
Desmand hus Associ Englisses (laus Laus struct)
Prepared by : Asset Engineer (level crossings)
A Date: 21 <sup>st</sup> January 2015 Andy Kenning
Checked by : Liability Negotiations Adviser
So
Steve Day
Approved by : Sponsor
MID
Sean Cronin
Accepted by : Route Enhancement Manager
Cio
Date: 22 <sup>nd</sup> January 2015
Colin Conway
Optional Signatories
Endorsed by : Director of Route Asset
Management
Date: Spiles 1000
Eliane Algaard
Endorsed by Level Crossing Manager WA
1/11/11/ Date: 12/02/15
Wayne Underwood
This document is the property of Network Rail. It shall not be reproduced in whole or in part, nor
disclosed to a third party without prior written permission. Copyright 2014 Network Rail
sopjight 2014 Helwork Itali

Document Ref: Camb-P1&2 TWAO		חסמ		
Issue: 1.0	RRD			
Date: 21 <sup>st</sup> January 2015	Page:	1	of	45



# **Document History**

Issue	Date	Originator	Modification
1.0	21-01-15	Andy Kenning	Initial Issue

# Endorsement

The information contained within this Route Requirements Document has been produced with the approval of the following Route Asset Managers:

Discipline	Name	Title	Signature	Date
Earthworks	lan Payne	Senior Asset Engineer	Not required for this RRD as no gauging is involved.	n/a
E&P	Carl Hunt	Route Asset Manager		
Gauging	Steve Valentine	Senior Asset Engineer	Not required for this RRD as no gauging is involved.	n/a
Signalling	Mike Essex	Route Asset Manager		
Structures	Anthony Dewar	Route Asset Manager	Not required for this RRD as no gauging is involved.	n/a
Telecoms	Andy Coleman	Senior asset Engineer		
Track	Nigel Wilson	Route Asset Manager		

Document Ref: Camb-P1&2 TWAO		RRD		
Issue: 1.0		ΝΝυ		
Date: 21 <sup>st</sup> January 2015	Page:	2	of	45



# Contents

1	Purpose	5
1.1	Background Information	5
1.2	Stakeholders	5
2	General Description of the Route	6
2.1	Route Objectives (Problem Statement)	6
2.2	Route Definition	6
2.3	Boundaries and Relationships	7
2.4 2.4 2.4 2.4 2.4	<ul><li>1.2 Dependencies</li><li>1.3 Constraints</li></ul>	
2.5	Whole Life Cost Analysis	9
2.6	Route Key Milestones and Configuration States	9
2.7	Route Acceptance Strategy	9
2.8	Route Security Assessment	9
3	Route Requirements	
3.1	Deliverables	
3.2	Safety Requirements	
3.3	General Scheme - Requirements	
3.4	Network Rail Asset Requirements E&P	
3.5	Network Rail Asset Requirements Signalling	
3.6	Network Rail Asset Requirements Track	
3.7	Network Rail Asset Requirements Telecoms	
3.8	Operational Requirements	
3.9	Performance Requirements	17
	ment Ref: Camb-P1&2 TWAO	RRD
Issue		
Date	21 <sup>st</sup> January 2015	Page: 3 of 45



3.10	Environmental Requirements	18
3.11	Reliability, Availability, Maintainability Requirements	18
3.12	Maintenance Requirements	18
Appendi	x A – Deliverables	20
Appendi	x B – References	20
Appendi	x C - Glossary2	20
Appendi	x D - Whole Life Cost Analysis	20
Appendi	x E - Additional Information2	20

Document Ref: Camb-P1&2 TWAO		RRD		
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	4	of	45



# **1** Purpose

The purpose of this RRD is to further develop the opportunity to close level crossings on Anglia Route within the county of Cambridgeshire. This RRD is to cover crossings that can be diverted or extinguished without the need to build bridges or large structures. These diversions or extinguishments shall be carried out using compulsory powers obtained by means of a Transport & Works Act Order.

## **1.1 Background Information**

An over arching CRD has been produced to explain in detail the Anglia Route strategy for achieving a crossing reduction in CP5. This also explains the different phases of the strategy, separate RRDs are to be produced for each county.

## 1.2 Stakeholders

The following stakeholders have been identified:

Name	Role	Contact	
Cambridgeshire	Highway authority		
County Council			
South	District Council		
Cambridgeshire			
East	District Council		
Cambridgeshire			
Fenland District	District Council		
Office of Rail	Governing Body		
Regulator			
Environment	Statutory consultee (flood	ł	
Agency	risk etc.)		
Natural England	Statutory consultee	T	
·	(environment)		
Steve Day	Liabilities Negotiations		
-	Advisor		
Katie Brown	Land Consents	Τ	
Hannah Briggs	Public Relations Manager	-	
Richard Schofield	Route Director (Anglia)		
Eliane Algaard	Director of Route Asset	T	
Ū	Management		
Carl Hunt	Route Asset Manager (E&P)	Γ	
Mike Essex	Route Asset Manager		
	(Signalling)		
Nigel Wilson	Route Asset Manager		
-	(Track)		
Dave Flatman	Route Telecoms Engineer		
	Route Level Crossing	T	
Wayne	reate Level erecenng		

Issue: 1.0		RRD		
Date: 21 <sup>st</sup> January 2015	Page:	5	of	45



Name	Role	Contact
Bram Davenport	Level Crossing Manger	
Brendan Lister	Level Crossing Manger	[
Kevin King	Level Crossing Manger	
John Prest	Level Crossing Manger	[
Sean Cronin	Sponsor	[
The Ramblers	User Group (walkers)	[
Sustrans	User Group (promoting non-	
	motorised transport)	
Open Spaces	User Group (promoting	
Society	access to land)	
Auto Cycle Union	User Group (motor vehicles)	

# **2** General Description of the Route

## 2.1 Route Objectives (Problem Statement)

#### **Closure difficulties**

Public footpaths and bridleways can be closed by rail crossing diversion or extinguishment orders (expedient in the interests of public safety) or normal public path orders (diversion to make more commodious/better serve the landowner/not necessary). However, all of these are subject to challenge which can result in public inquiry, where success is not guaranteed. This is therefore a risky and time-consuming strategy. The legal costs of a basic application are around £3k–4k.

All pubic highways can be closed or downgraded by application to a magistrate's court, on the grounds that they are not needed for public use, or should be diverted. Again, this is risky as there is no guarantee magistrates will agree to make an Order. Cost of an application about £3k.

### 2.2 Route Definition

The best way to close public highways is through a Transport and Works Act Order. In that way, all proposed changes and consents can be consulted in advance, bridges provided where appropriate, and we can argue using the greater public benefit of improved rail services.

Some of the crossings listed in this remit are affected by proposed speed increases and some are subject to increased freight traffic. The proposed freight traffic will utilise trains up to 775metres in length, this causes problems when held at signals where the train may standback over level crossings.

There are a number of footpath crossings throughout Cambridgeshire County which have the opportunity to be diverted or extinguished from crossing the railway line at grade to a grade separated crossing point.

Each crossing listed in section 2.3 shall have the following assessments carried out and providing that it can be achieved, the next assessment shall be carried out;

Document Ref: Camb-P1&2 TWAO		RBD		
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	6	of	45



- 1. The diversion assessed for build ability based on the potential users and their physical abilities. This may be determined by other physical features along the footpath such as the presence of stiles or steps.
- 2. Diversity impact assessment needs to be carried out (to be completed by Network Rail team).
- 3. A brief design shall be produced to capture the alterations required.
- 4. Land clearance application made and approved.
- 5. The cost of each diversion shall be created against the design. These costs shall include recovery of all the current crossing assets (including whistle boards if fitted) and making good the boundary fencing to ensure there are no trespass issues following the diversion. Costs shall also include if any alterations required to the OLE (this shall be indicative at this stage, AIP shall be produced at GRIP3).
- 6. Environmental impact assessment for the impact of the diversion / extinguishment / downgrading.
- 7. Pre-Consultation for the diversion / extinguishment.
- 8. It is assumed that the diversions can be carried out within the Network Rail land ownership boundary. If not then land owner consent will be required for route of public path.
- 9. If land consents are required a land search shall be completed to identify the land owner/s.

### 2.3 Boundaries and Relationships

Strategic Route:	D
Route Number:	
Operating Route:	Anglia
ELR and Mileage:	BGK, SBR, EMP. ETN, SOB, CCH
OS Ref:	
Asset Type:	Level crossing
Asset Address (if applicable):	

The crossings within this remit are as follows;

#### Phase 1 - Mainlines

Name	Location	Туре	Status	Proposal
Websters	BGK 53m 00ch	FPS	Public Footpath	Diversion to new overbridge
Chittering	BGK 64m 23ch	FPS	Public Footpath	Diversion
Nairns	BGK 65m 46ch	UWCT	Accommodation	Extinguishment
West River Bridge	BGK 67m 22ch	FPS	Public Footpath	Diversion
No.20	SBR 47m 51ch	FPS	Public Footpath	Diversion
Flambards	SBR 48m 12ch	FPS	Public Footpath	Diversion
Barrington Road	SBR 50m 73ch	FPW	Public Footpath	Extinguishment
No.37	SBR 52m 75ch	FPW	Public Footpath	Diversion
Ely North Jcn	EMP 72m 01ch	FPS	Public Footpath	Diversion
Document Ref: Can	nb-P1&2 TWAO			RRD
Issue: 1.0				
Date: 21 <sup>st</sup> January 2	2015		Pa	age: 7 of 45



Name	Location	Туре	Status	Proposal
Second Drove	EMP 72m 55ch	FPS	Public Footpath	Extinguishment
Silt Drove	EMP 84m 69ch	UWCT	Public Road	Extinguishment
Middle Drove	EMP 87m 75ch	UWCT	Public Road	Downgrade to footpath & registered user
Eastrea Cross Drove	EMP 93m 05ch	FPS	Public Footpath	Diversion
Brick Yard Drove	EMP 93m 43ch	FPS	Public Footpath	Extinguishment
Prickwillow No.1	ETN 74m 28ch	FPS	Public Footpath	Diversion
Prickwillow No.2	ETN 74m 30ch	FPS	Public Footpath	Diversion
Munceys	SOB2 4m 61ch	FPS	Public Footpath	Diversion
Wicken Road	SOB2 6m 44ch	FPW	Public Footpath	Diversion
Leonard	SOB2 7m 17ch	FPK	Public Footpath	Diversion
Newmarket Bridge	SOB2 11m 75ch	FPW	Public Footpath	Diversion
Wells Engine	SOB2 12m 03ch	FPW	Public Footpath	Diversion

#### Phase 2 – Branchlines

Name	Location	Туре	Status	Proposal
Adelaide	BGK 72m 71ch	FPS	Public Footpath	Extinguishment
Cross Keys	BGK 73m 18ch	FPS	Public Footpath	Diversion
Clayway	BGK 75m 25ch	FPS	Public Footpath	Extinguishment
Poplar Drove	BGK 76m 71ch	UWCT	Occupation	Extinguishment
Willow Row	BGK 77m 16ch	UWC	Byway open to all traffic	Downgrade to a footpath
Black Horse Drove	BGK 79m 19ch	UWCM	Public Road	Downgrade to occupation
Cassells	CCH 8m 5ch	FPG	Public Footpath	Diversion
Westley Road	CCH 8m 74ch	UWCT	Public Road	Downgrade to footpath & registered user

## 2.4 Assumptions, Dependencies, Constraints & Risks

### 2.4.1 Assumptions

Reference	Details
A-CAMB-1	That the diversionary routes are buildable
A-CAMB-2	That funding will be made available for the diversions to be built
A-CAMB-3	That the diversions can be carried out within the existing Network Rail land ownership
A-CAMB-4	Any required land consents will be available

Document Ref: Camb-P1&2 TWAO	RRD			
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	8	of	45



#### 2.4.2 Dependencies

Reference	Details
D-CAMB-1	That Liabilities are able to support the TWAO application

#### 2.4.3 Constraints

Reference	Details
C-CAMB-1	This requirement is to be restricted to the County of Cambridgeshire.
C-CAMB-2	This remit is not to cover the construction of large structures such as bridges or underpasses.

#### 2.4.4 Risks

Reference	Details
R-CAMB-1	Not all the diversionary route will be buildable
R-CAMB-2	That there may be alternative proposals from external stakeholders
R-CAMB-3	That the secretary of State for Transport will not sign off the order

### 2.5 Whole Life Cost Analysis

Whole Life Cost Modelling (WLCM) will be applied to the later phases. Phases 1&2 do not need WLCM produced for them provided that the over all cost is equal to or less than the risk reduction cost.

Alterations to the Overhead Line Equipment (OLE) shall be subject to a Cost Benefit Analysis to understand the benefit in altering the OLE wire heights. This is to compare the options of altering a crossing at a time, or waiting until either wire renewals, or other improvement projects.

### 2.6 Route Key Milestones and Configuration States

It is anticipated that Phase 1 & 2 crossings shall be identified by the end of CP5 year 1. During CP5 year 2 it is expected that Phase 1 & 2 crossings shall be developed into buildable solutions and costed. Key milestones would be;

- Conformation that the diversions are buildable
- Design for each diversion that is buildable
- Costs produced for each of the designed diversions

### 2.7 Route Acceptance Strategy

This scheme shall follow GRIP and acceptance for each stage shall be at each stage gate as shown in the project programme.

Once the diversions have been designed, consulted and costed they shall be presented to the Sponsor for acceptance and inclusion in the Transport & Works Order, before the completion of GRIP3. This will allow the Sponsor to 'group' projects into TWAO to keep costs down and provide a strategic approach to the TWAO application.

### 2.8 Route Security Assessment

Nothing identified at the time of writing.

Document Ref: Camb-P1&2 TWAO	RRD			
Issue: 1.0	KKD			
Date: 21 <sup>st</sup> January 2015	Page:	9	of	45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Suppo Informa		Assumption
		3 Route Requirements					
RR- CambP1&P 2-1101	RAM/Sponsor	3.1 Deliverables The deliverables listed in Appendix A shall be produced and delivered at the required GRIP stage.	High	Deliverables listed in Appendix A are produced to the satisfaction of the RAM / Sponsors at the identified GRIP stages.	None identif	ied	None
		3.2 Safety Requirements					
RR- CambP1&P 2-1121	CR-CP5LX-1101	The Scheme shall be delivered in accordance with the Common Safety Method (CSM)	High	<ul> <li>Preliminary System Definition</li> <li>CSM Assessment Completed and Category assigned</li> <li>CSM Deliverables completed id the scheme deemed to be "significant change".</li> </ul>	None identif	ied	None
RR- CambP1&P 2-1122	CR- CP5LX -1102	The scheme shall be delivered in accordance with the CDM Regulations	High	<ul> <li>Personnel (posts) are designated and responsibilities discharged</li> <li>Demonstrable evidence of compliance is provided</li> </ul>	Constructior and Manage Regulations	ement)	None
Document Ret Issue: 1.0	: Camb-P1&2 TWAO	•		RRD			
Date: 21 <sup>st</sup> Jan	uary 2015					Page:	10 of 45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Supporting Information	Assumption
RR- CambP1&P 2-1123	CR- CP5LX -1103	All meetings in connection with this project shall have a standing agenda item of Safety at the beginning of each meeting.	High	Meeting agendas and minutes shall be held as part of the project documentation file.	None identified	None
RR- CambP1&P 2-1124	CR- CP5LX -1104	The closed level crossings shall be inaccessible to the public and appropriately fenced over.	High	Compliant to the Company standard for lineside fencing.	None identified	None
		3.3 General Scheme - Requirements				
RR- CambP1&P 2-1131	CR- CP5LX -1111	The Sponsor Instruction and Client Requirements Document Contents shall be adhered to.	High	Demonstrable evidence of compliance.	None identified	None
RR- CambP1&P 2-1132	CR- CP5LX -1112	The scheme shall be delivered in accordance with GRIP	High	Completed and approved GRIP stage gate at intervals laid down in the Sponsor Instruction.	None identified	None
RR- CambP1&P 2-1133	CR- CP5LX -1113	The diverted / extinguished rights of way shall be updated on the definitive maps for the county	High	Definitive map updated to show correct status.	None identified	None
RR- CambP1&P 2-1134	CR- CP5LX -1114	Design Guidance for Accessibility for Reduced Mobility shall be followed during early development and design.	High	All Accessibility requirements are provided (including step free access to new platforms and fire escape	None identified	Only used where access to a station is required

Document Ref: Camb-P1&2 TWAO	DDI			
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	11	of	45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Supporting Information	Assumption
				arrangements). Where this is not possible mitigation measures and safe systems must be provided.		
RR- CambP1&P 2-1135	CR- CP5LX -1115	Governing act regarding equality. In relation to this project particular attention must be given to provide access for those with reduced mobility and sight.	High	Demonstrable evidence of compliance and inclusion in development and design.	None identified	None
RR- CambP1&P 2-1136	CR- CP5LX -1116	New footpath widths shall be 2metres wide as a minimum	High	New path to be of the minimum width.	None identified	None
RR- CambP1&P 2-1137	CR- CP5LX -1117	Any new bridleway paths shall be 3metres wide as a minimum	High	New path to be of the minimum width.	None identified	None
RR- CambP1&P 2-1138	CR- CP5LX -1118	Any footpath crossing that appears to have been abandoned shall be planned to be extinguished in phase 1 or phase 2.	High	No abandoned footpaths left on the Anglia Route.	None identified	None
RR- CambP1&P 2-1139	CR- CP5LX -1119	Any footpath / bridleway crossing that have a near and practical alternative crossing point that provides a better level of protection shall be diverted in phase 1 or phase 2.	High	No footpaths / bridleways are left remaining when there is a close by alternative crossing point.	None identified	None
RR- CambP1&P 2-1140	CR- CP5LX -1120	Any footpath / bridleway that can not be removed from the railway network in phase 1 or	Medium	Footpath / bridleways that were not extinguished or	None identified	None

Document Ref: Camb-P1&2 TWAO	DDL		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 1	2 of	45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Supporting Information	Assumption
		phase 2 shall be developed for phase 3.		diverted are planned to be provided with a bridge.		
RR- CambP1&P 2-1141	CR- CP5LX -1123	Diversity Impact Assessment	High	Production of a report detailing the diversity impact of the proposed changes.	None identified	None
		3.4 Network Rail Asset Requirements E&P				
RR- CambP1&P 2-1201	CR-CP5LX-1171	Where a level crossing is being removed the Overhead Line Equipment (OLE) contact wires shall be adjusted to be as near to the nominal wire height of 4.7metres as practical.	Low	Contact wires are at the optimum height for that area of line.	A cost benefit analysis shall be applied to understand the operational benefits of altering the wire heights per crossing	That the current wire heights are compliant to standards (run-ins / run-outs).
RR- CambP1&P 2-1202	CR-CP5LX-1172	Where a level crossing is being removed and the current (OLE) contact wires arrangements are not compliant to standard, the wire heights shall be adjusted to be as near to the nominal wire height of 4.7metres as practical.	High	Contact wires are at the optimum height for that area of line.	Records of existing deficient wire heights (including run-in / run- outs)	
RR- CambP1&P 2-1203	CR-CP5LX-1173	Where new bridges are to be constructed they shall be bonded to the traction return where appropriate.	High	New structures are suitably bonded to be compliant to Network Rail company standards.	None identified	

Document Ref: Camb-P1&2 TWAO	DDD		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 1	3 of	45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Supporting Information	Assumption
		3.5 Network Rail Asset Requirements Signalling				
RR- CambP1&P 2-1211	CR-CP5LX-1182	Where crossings are removed that have telephones fitted the signallers display system (diagram, panel or VSCS) shall be updated to shown the removal.	High	Signallers display system updated to reflect the current state of the infrastructure.	None identified	None
RR- CambP1&P 2-1212	CR-CP5LX-1183	Where crossings are removed the Signalling RAM shall be informed so that a plan can be put in place to get them removed from the Signalling diagrams (if shown).	High	That it is recorded where footpath or UWCs are recovered and the Signalling RAM is presented with this information.	None identified	These alterations shall be managed by means of a records deficiency form and updated when the record is next worked on.
RR- CambP1&P 2-1213	CR-CP5LX-1184	Where whistle boards are to be removed, the Signalling RAM shall be informed so that a plan can be put in place to remove them from the signalling diagrams.	High	That it is recorded where whistle boards are recovered and the Signalling RAM is presented with this information.	None identified	These alterations shall be managed by means of a records deficiency form and updated when the record is next worked on.

Document Ref: Camb-P1&2 TWAO	DD	n		
Issue: 1.0		U		
Date: 21 <sup>st</sup> January 2015	Page:	14	of	45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Supporting Information	Assumption
		3.6 Network Rail Asset Requirements Track				
RR- CambP1&P 2-1221	CR-CP5LX-1191	Crossing deck (if fitted) shall be removed (including edge beams, if fitted) and track inspected to ensure that all the track components are still serviceable.	High	No evidence of crossing on site & track components signed as fit for purpose.	None identified	None
RR- CambP1&P 2-1222	CR-CP5LX-1192	Where a crossing deck has been removed sleeper spacing shall be checked and if required corrected with serviceable spares to match the existing assets.	Medium	Sleeper spacing matches that of the approaches and all track components are of the same type.	None identified	None
RR- CambP1&P 2-1223	CR-CP5LX-1193	Where level crossings have been removed the ballast shoulder and cribs shall be reinstated to provide suitable track support	High	Track support system shall be in accordance with Network Rail Company standard.	None identified	None
RR- CambP1&P 2-1224	CR-CP5LX-1194	Where signalling equipment has been involved and train detection is reduced, any redundant Insulated Rail Joints (IRJ) shall be removed from the track. If in Continuous Welded Rail the rail shall be stressed to Level 1 (if <36metres of new rail) or level 2 (if > 36metres).	High	Redundant IRJs removed and stressing certificates provided	None identified	None

Document Ref: Camb-P1&2 TWAO	DDI			
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	15 c	of	45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Supporting Information	Assumption
		3.7 Network Rail Asset Requirements Telecoms				
RR- CambP1&P 2-1231	CR-CP5LX-1201	Where telephones are present they shall be recovered in working order and returned to be offered to the RCE and or NRT Central Stores (tie cabling shall be recovered and scraped).	High	Phones, posts, and bases removed including cabling.	None identified	None
RR- CambP1&P 2-1232	CR-CP5LX-1202	Where telephones are displayed on a telephone concentrator, these shall be removed from the system.	High	Telephone concentrator updated to reflect the current state of the infrastructure.	None identified	None
		3.8 Operational Requirements				
RR- CambP1&P 2-1241	CR-CP5LX-1231	Where whistle boards are to be removed these shall only be removed once published in the WON.	High	Whistle boards removed from the infrastructure.	None identified	None
RR- CambP1&P 2-1242	CR-CP5LX-1232	Where crossings to be removed are fitted with a phone, this shall only be done once it has been published in the WON.	High	Sectional Appendix updated to reflect the current state of the infrastructure.	None identified	None

Document Ref: Camb-P1&2 TWAO	DE	חכ		
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	16	of	45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Supporting Information	Assumption
RR- CambP1&P 2-1243	CR-CP5LX-1233	Where crossings to be removed are fitted with a phone, this shall only be done once Network Change has been done to remove them from the Sectional Appendix	High	Approved Network Change	None identified	None
		3.9 Performance Requirements				
RR- CambP1&P 2-1251	CR- CP5LX -1131	Any temporary TSR's that are in place as a result of the crossing having insufficient sighting shall be removed once the crossing is closed.	Medium	Removal of the TSR	Operational publications will detail where and what speeds are in force.	None
RR- CambP1&P 2-1252	CR- CP5LX -1132	Any operational restrictions regarding the standing of trains at signals due to the train blocking the footpath shall be removed.	Medium	Removal of local instruction	None identified	Only applicable to crossing where standage is an issue
RR- CambP1&P 2-1253	CR- CP5LX -1133	Where a PSR exists due to sighting requirements of a crossing that is being removed, the project shall investigate the potential of removing the PSR and increasing the line speed.	Low	Increase in line speed over the section of line where the crossing used to be located.	None identified	That the other railway infrastructure can withstand a speed increase.

Document Ref: Camb-P1&2 TWAO	חסס		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 17	7 of	45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Suppo Inform		Assumption
		3.10 Environmental Requirements					
RR- CambP1&P 2-1261	CR-CP5LX-1141	Adherence to corporate policies in development, design and construction.	High	Production of the Environmental Impact Assessment for suitable crossings	None identif	ied	None
		3.11 Reliability, Availability, Maintainability Requirements					
RR- CambP1&P 2-1281	CR-CP5LX-1161	Where crossings are closed; Ellipse shall be updated to remove the Maintenance Schedulable Tasks (MST) from the maintainers work bank. This shall cover all disciplines.	High	Ellipse data updated	None identif	ied	None
RR- CambP1&P 2-1291	CR-CP5LX-1162	Where crossings are closed ALCRM is updated to show the crossing as closed and no longer part of the network.	High	ALCRM data updated	None identif	ied	None
		3.12 Maintenance Requirements					
RR- CambP1&P 2-1301	CR-CP5LX-1151	Any roadway that is built to be used as a public highway shall be built to be adopted by the Highway Authority for on going maintenance	High	Adoption of the new roadway by the Highways Authority	None identified None		None
Document Re Issue: 1.0	f: Camb-P1&2 TWAO						RRD
Date: 21 <sup>st</sup> Jan	uary 2015					Page:	18 of 45



Reqt ID	Source Reference	Requirement and Heading	Priority	Acceptance Criteria	Supporting Information	Assumption
RR- CambP1&P 2-1302	CR-CP5LX-1152	Where assets are removed from the railway the appropriate data base shall be update to reflect the current state of the railway. This shall include (but not limited to) such systems as Ellipse, GEOGIS.	High	Asset data records correctly showing the status of the assets.	None identified	None

Document Ref: Camb-P1&2 TWAO	חסס		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 19	) of	45



# **Appendix A – Deliverables**

See attached project characterisation spreadsheet detailing the project deliverables.

# **Appendix B – References**

Anglia CP5 Level Crossing Reduction Strategy (CP5 Xing Reduction – Issue 1).

See pages 21 to 45 for maps of the crossings and their proposed alterations.

## **Appendix C - Glossary**

Abbreviation	Description
CRD	Client Requirements Document
DRRD	Detailed Route Requirements Document
IP	Infrastructure Projects
RAM	Route Asset Manager
RRD	Route Requirements Document
WLC	Whole Life Cost
TWAO	Transport & Works Act Order
PRoW	Public Right of Way
ALCRM	All level Crossings Risk Model
WON	Weekly Operating Notice
RCE	Route Communications Engineer
NRT	Network Rail Telecoms
OHLE	OverHead Line Equipment
VSCS	Video Screen Control System
IRJ	Insulated Rail Joint
TSR	Temporary Speed Restriction
PSR	Permanent Speed Restriction

# **Appendix D - Whole Life Cost Analysis**

Not applicable to this phase.


# **Appendix E - Additional Information**

Nothing identified at the time of writing.

Document Ref: Camb-P1&2 TWAO		חסס		
Issue: 1.0		κκυ		
Date: 21 <sup>st</sup> January 2015	Page:	20	of	45




#### Phase 1 – Mainline Maps



Websters (diversion to new foot bridge)

Document Ref: Camb-P1&2 TWAO	חסס		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 2 <sup>°</sup>	of	45






Jack O'Tell & Chittering footpath (divert to J O'T)

Document Ref: Camb-P1&2 TWAO	חסס		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 22	of	45






#### Nairns

Document Ref: Camb-P1&2 TWAO	DDD		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 23	< OT	45






West River (divert to underbridge)

Document Ref: Camb-P1&2 TWAO	חסס		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 24	l of	45








Document Ref: Camb-P1&2 TWAO	DDD		
Issue: 1.0		,	
Date: 21 <sup>st</sup> January 2015	Page: 2	5 of	45






Flambards (diversion to underbridge)

Document Ref: Camb-P1&2 TWAO	D	חכ		
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	26	of	45






Barrington Road (extinguishment)

Document Ref: Camb-P1&2 TWAO	DD			
Issue: 1.0	RKD			
Date: 21 <sup>st</sup> January 2015	Page:	27	of	45






No.37 footpath (diversion to overbridge to the north)


Document Ref: Camb-P1&2 TWAO	RRD		
Issue: 1.0		)	
Date: 21 <sup>st</sup> January 2015	Page: 2	28 of	45






Document Ref: Camb-P1&2 TWAO	RRD			
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	29	of	45





Document Ref: Camb-P1&2 TWAO	חסס		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 30	of	45






#### Silt Drove

Document Ref: Camb-P1&2 TWAO	חסס		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 31	of	45






Middle Drove (downgrade to footpath)

Document Ref: Camb-P1&2 TWAO	RBD		
Issue: 1.0	KKU		
Date: 21 <sup>st</sup> January 2015	Page: 32	of	45





Document Ref: Camb-P1&2 TWAO	DD			
Issue: 1.0	КК	U		
Date: 21 <sup>st</sup> January 2015	Page:	33	of	45






Fen Lots Drove & Brick Yard Drove (extinguishment)


Document Ref: Camb-P1&2 TWAO	D	חכ		
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	34	of	45












Munceys (diversion along railway)

Document Ref: Camb-P1&2 TWAO	RRD			
Issue: 1.0	KKU			
Date: 21 <sup>st</sup> January 2015	Page:	36	of	45







Wicken Road (diversion along railway)

Document Ref: Camb-P1&2 TWAO	RRD		
Issue: 1.0	KKU		
Date: 21 <sup>st</sup> January 2015	Page: 37	7 of	45










Wells Engine & Newmarket Bridge (divert to underbridge)

Document Ref: Camb-P1&2 TWAO	RRD		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 39	of	45






Cross Keys & Adelaide FPS (divert to underbridge at cross keys?)


Document Ref: Camb-P1&2 TWAO	DD			
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	40	of	45





Document Ref: Camb-P1&2 TWAO	PPD			
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	41	of	45





Willow Row (downgrade to footpath) & Poplar Drove (extinguishment)

Document Ref: Camb-P1&2 TWAO	PPD		
Issue: 1.0			
Date: 21 <sup>st</sup> January 2015	Page: 42	of	45





Black Horse Drove


Document Ref: Camb-P1&2 TWAO	DDD			
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	43 (	of	45





Cassells (divert to Brinkley Road)

Document Ref: Camb-P1&2 TWAO	PPD			
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	44	of	45



Westley Road (downgrade to footpath)

Document Ref: Camb-P1&2 TWAO	PPD			
Issue: 1.0				
Date: 21 <sup>st</sup> January 2015	Page:	45	of	45